

Declaration of Performance

Product/DoP Ref: 032CPR13 Product-type: L10

Product intended to be used in walls and partitions

| Manufacturer | Notified Body | |
|--|--|--|
| IG (Lintels) Ltd., Avondale Road, Cwmbran, Gwent, NP44 1XY | Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ | |
| IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type L10 is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2003. | Ceram No. 1289, conducted determination of the product-type. The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2003. The AVCP for the product is system 3. | |

| Essential Characteristics | | Lintel Length (mm) | | | LEN |
|--|--|---|----------------|---|-----|
| | | 0600-1200 | 1350-1800 | 1950-2700 | hEN |
| Load Bearing Capacity (kN) Total UDL | Figures shown are safe working loads | 4 | 8 | 10 | |
| Deflection Und | er Load | Less than Effective Span/325 at maximum safe working load | | Effective Span/325 at maximum safe working load | |
| Mass Per Unit Area | | NPD | | | 003 |
| Water Absorption | | Zero | | | |
| Thermal Resistance (W/mk) 50 | | | EN 845-2: 2003 | | |
| Resistance to | o Fire | NPD (Contact IG Technical Department for information) | | | |
| Durabilit (against corre | | L14 | | | |
| Durabilit (against freeze | | Resistant | | | |
| Dangerous Substances None | | | | | |

Signed for on behalf of the manufacturer by:

Denix Metalare

| Name: | Derrick | McFarland, | Managing | Director |
|----------|---------|----------------|--------------|----------|
| Ivallie. | Dellick | IVICI allaliu, | ivialiaqiiiq | Director |

At: Cookstown **On:** 30 / 06 / 2015

Signature: