

# Decking Screws



## Decking Screw - Countersunk

Exterior (Green Organic)



**Superior Corrosion Resistance!**



Urban & industrial areas with a low salt atmosphere

An economic but highly effective softwood decking screw.

Plated to withstand up to 500 hours in a salt spray cabinet and designed to give a rapid installation and a secure fixing.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>BOX</b>					
50TDECK	4.5 x 50	PZ2	200	15	540
60TDECK	4.5 x 60	PZ2	200	15	540
70TDECK	4.5 x 70	PZ2	200	16	384
<b>TUB (DRIVER BIT INCLUDED)</b>					
60TDECK1500	4.5 x 60	PZ2	1,500	2	72
TYPE - IDD			SUB TYPE - IDD03		

## Decking Screw - Countersunk

A2 Stainless Steel



**Superior Corrosion Resistance!**



Urban & industrial areas with a moderate salt atmosphere

An economic but highly effective softwood decking screw.

Manufactured from A2 Stainless Steel. Offering superior corrosion resistance making it ideal for multiple external applications, especially for the construction of decking platforms. Stainless steel must be used where there is corrosive environment and/or the base material has inherent corrosive characteristics e.g. Green Oak.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>TUB</b>					
50TDECKSS	4.5 x 50	PZ2	250	4	228
65TDECKSS	4.5 x 65	PZ2	250	4	228
TYPE - IDD			SUB TYPE - IDD02		

# Collated Decking Screws



**C2**  
**DECK-FIX**  
**PREMIUM SCREW**

DESIGNED FOR DECKING PLATFORMS & EXTERNAL TIMBER CONSTRUCTION



## C2 Deck-Fix Collated Decking Screw

Exterior (Green Organic)



A premium decking screw using the C2 twin-cut technology.

See page 31 for more information about the C2 Deck-Fix



Urban & industrial areas with a low salt atmosphere

Product Code	Size (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
<b>BOX</b>				
65C2DCOLL	4.5 x 65	500	10	240
TYPE - COL		SUB TYPE - COL08		