



TIMco

IN-DEX™

TIMBER SCREWS

DESIGNED FOR OUTDOOR APPLICATIONS

Designed as an alternative to the traditional coach screw mainly used for timber to timber applications. Coated with a patented multi-layer corrosion resistant plating, this screw is ideal for outdoor applications.

Stainless Steel must be used where there is a corrosive environment and/or where the base material has inherent corrosive characteristics eg: Green Oak.

Standard:

Packaging Options:



BOX



TUBE



TIMBAG



TIMPAC

Available in:


Stainless Steel

EXTERIOR

Head Types:



HEX HEAD



WAFER HEAD

PATENTED
CORROSION
RESISTANT
PLATING

MAGNETIC SOCKET DRIVER BIT

Used for installing 8 mm hex headed fasteners with standard drill drivers

TIMco Code:
IN8SDB



HEX/WAFER HEAD

8mm hex head countersunk with a fixed washer or wafer head with TX30/TX40 recess.

LONG LASTING PLATING

Exterior & A2 / A4 Stainless Steel.

SUPERIOR CORROSION RESISTANCE!

Salt spray resistance tested in accordance to BS EN 9227:2012.

PATENTED MOLECULAR LUBRICATION

Patented lubrication, designed to enhance screw insertion time and provides greater resistance to corrosion.

HELIX

To remove debris and improve clamping.

50° DEEP SINGLE THREAD

To provide secure fixing with high pull-out resistance

TYPE 17 SLASH

To reduce torque and the likelihood of the timber splitting when the screw is inserted close to the edge.

25° SHARP POINT

Sharp point and single threading for a fast start, easy penetration and improved thread acceptance.

The TIMco **IN-DEX**™ timber, decking and external screws carry the CE mark in compliance with the Construction Products Regulations (Eurocode 5 EN1995-1-1)